

Cone 70



Part Number JR01519



Features

- Energy saving
- Full intensity from switch on
- Interchangeable LED engine
- Wide range of LED CCTs and reflectors
- Warm Dim 3000°K-2000°K option
- CREE 2 step MacAdam LEDs
- CRI >95 available on request
- Long life L70 50,000 hrs based on LM-80 & TM-21 applicable test data
- Remote constant current driver with S.E.L.V. output
- Mains phase, 0-10V and DALI dimming options available
- 5 Year warranty

Luminaire Specification

Height	B : 95mm C : 115mm
Bezel	Ø75mm
Hole cut-out	Ø70mm
Luminaire material	Aluminium with textured powder coat finish.
IP Rating	IP44

LED Specification

LED	B / C : CREE CXB
Output	B / 8.6W : 1038lm (120lm/W) C / 12W : 1600lm (134lm/W) CW / 13W : 1000lm (77lm/W)
CRI/CCT	90Ra : 2700°K, 3000°K 80Ra : 4000°K, 5000°K 90Ra : Warm Dim (CW) 3000°K-2000°K >90 & >95 on request
Optics	Narrow 20°, wide 40°, flood 60°
Drive current	B : 250mA, C / CW : 350mA

Ordering Information example 2784.233C

Model	Finish	LED CCT	Driver	Version
2782. Narrow 20°	1 White	2 2700°K	2 Phase dimming	B 8.6W
2784. Wide 40°	2 Black	3 3000°K	3 0-10V Dimming	C 12W
2786. Flood 60°	5 Aluminium	4 4000°K	4 DALI Dimming	CW 13W [®]
	7 Silver	5 5000°K		