


Eyelet Q and R



Part Number JR07255



Finishing casing

Material	Aluminium 6026
Colour	Embossed white RAL 9003
Processing	Powder coating

Finish	Black, Grey, White
Type	Surface
Installation Position	Wall Lights, Ceiling, Floor
Installation Environment	Indoor
Light Source	LED
Optics	Spot 15°, Flood 30°, Wide Flood 60°
Light Emission Direction	Frontal
Power	1w or 2 w
Source Lumens	41, 44, 47, 79, 84, 144, 153, 154, 169, 172, 180 lm
Current Intensity	350mA
CCT/Tone	2700 K, 3000 K, 4000 K
Colour Rendering Index	80 Ra
C.C / C.V	C.C
Safety Class	3
IP	IP40
IK	IK03
Glow Wire Test	850°
Direct Mounting On Normally Flammable Surfaces	Yes
CE	Yes
Operating Temperature	-20 / +50
Driver Included	No
Dimmable Article	DALI - 1-10V
Directional	Swivelling
Total Angle	180°
Tilting	No
Walk-over	No
Drive-over	No
Cable Included	Yes
Cable Length	1 m
Resin Potting	No
Typers of Light Emission	Single Emission
Net Weight	0.02kg
Electrostatic Discharge Protection	No
Surge Protection	No
Product Techological Characteristics	TVS
Ordinary Temperature on the glass	35°C